



CONNECTION: ACCEPTS PRE-SWAGED 1 2" TUBE WITH NUT AND FERRULE  
 NOMINAL CRACKING PRESSURE: 10 - 20 PSI



CONNECTION: ACCEPTS PRE-SWAGED 3 4 TUBE WITH NUT AND FERRULE  
 NOMINAL CRACKING PRESSURE: 10 - 20 PSI



CONNECTION: THREADS DIRECTLY INTO SAEJ1926, -8 PORT  
 (NOMINAL 1 2" TUBE OD)  
 NOMINAL CRACKING PRESSURE: 10 - 20 PSI



CONNECTION: THREADS DIRECTLY INTO 3 4" NPT FITTING  
 NOMINAL CRACKING PRESSURE: 10 - 20 PSI



CONNECTION: ACCEPTS PRE-SWAGED 3 4 TUBE WITH NUT AND FERRULE  
 NOMINAL CRACKING PRESSURE: 10 - 20 PSI

<b>THIS DRAWING CONTAINS PROPRIETARY INFORMATION AND MAY NOT BE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT.</b>			
UNLESS OTHERWISE STATED:			
ALL DIMENSIONS ARE IN IMPERIAL INCHES			
TOLERANCE:			
ONE PLACE DEC. = ±.05			
TWO PLACE DEC. = ±.01			
THREE PLACE DEC. = ±.005			
ANGLE = ± 1'			
MATERIAL:			
FINISH:		SIZE	DWG. NO.
		C	VC SERIES VENT CAPS
DO NOT SCALE DRAWING		SCALE:	WEIGHT:
			SHEET 1 OF 1
		TITLE: VC SERIES VENT CAPS	
		REV	NC